

Features

Input DC.....DC 11V to DC 15V at 10A max, for the car
Input AC.....AC 100 to 240V 50/60Hz at 1.6A max
Output DC..... 15V/16V 18V/19V/20V@5A;
21V/22V/24V @100W max
USB DC.....5V with **1A**

Specifications

Rated input voltage (50-60Hz).....AC100-240V DC 11V-15V
Input rated current.....1.6 A
Input power140VA
Outpower (max.)100W
Efficiency>85% (TYP)
Output voltage.....DC 15V-24V
Output current**5A** (max)
Overload protectionYes
Short circuit protectionYes
Line regulation.....+/- 5%
Load regulation.....+/- 5%

Weight500g
Dimensions144 x 66 x 34 mm
Operating temperature0° C to 40° C
Humidity20% to 80%
Warranty2 years

8 Pins function

Type & output	connector size (mm)	Fit for notebook
15V/16V 18V/19V/20V@5A 21V/22V/24V @100W max	6.0*4.4 with pin Inside (Black)	Sony, Fujitsu, Samsung, Toshiba, NEC, Liteon,Toshiba,Acer,Dell,IBM,ThinkPad, HP,Delta,Compaq, EMC,MSI,Gateway, BenQ, ASUS, LG, Sharp, Ect other PC with left connector and under 100W.
	6.3*3.0(Green)	
	5.5*2.5 (white)	
	5.5*2.1 (Blue)	
	5.5*1.7 (Yellow)	
	4.8*1.7 (Yellow)	
	4.0*1.7 (Yellow)	
3.5*1.35 (Red)		